

G240514A

ORIGINAL

1. Exporter's Name and Address, Country		CERTIFICATE NO. F247666145590009			
2. Consignee's Name and Address, Country		CERTIFICATE OF ORIGIN CHINA-PAKISTAN FTA (Combined Declaration and Certificate) Issued in <u>THE PEOPLE'S REPUBLIC OF CHINA</u> (Country) See Instructions Overleaf			
3. Producer's Name and Address, Country					
4. Means of transport and route (as far as known) Departure Date JUN. 30, 2024 Vessel /Flight/Train/Vehicle No. UNION GLORY/24157 Port of loading JINGTANG PORT IN CHINA Port of discharge KARACHI PORT, PAKISTAN		5. For Official Use Only Verification: origin.customs.gov.cn ☐ Preferential Treatment Given Under China-Pakistan FTA Free Trade Area Preferential Tariff ☐ Preferential Treatment Not Given (Please state reason/s) Signature of Authorized Signatory of the importing Country			
6. Item number	7. Marks and numbers on packages; Number and kind of packages; description of goods; HS code of the importing country	8. Origin Criterion	9. Gross Weight, Quantity and FOB value	10. Number and date of invoices	11. Remarks
1	SIXTY THREE (63) PIECES OF PRIME HOT ROLLED STEEL PLATES STEEL GRADE: A516 GR70 HS CODE: 7208.51 DOCUMENTARY CREDIT NUMBER: LCSF953502462-24 *** **	"P"	242.140MT N.W. 242.140MT G.W. USD: 139956.92	24XS-CK-0509-2 JUN. 18, 2024	*****
Marks and numbers on packages: N/M					
12. Declaration by the exporter The undersigned hereby declares that the above details and statement are correct: that all the goods were produced in (Country) and that they comply with the origin requirements specified for these goods in the China-Pakistan Free Trade Area Preferential Tariff for the goods exported to PAKISTAN (Importing country) Shijiazhuang, China, JUL 23, 2024 Place and date, signature and stamp of authorized signatory		13. Certification It is hereby certified, on the basis of control carried out, that the declaration by the exporter is correct. ISSUED RETROACTIVELY  Shijiazhuang, China, JUL 23, 2024 Place and date, signature and stamp of certifying authority			

2030059

产品质量证明书
MILL TEST CERTIFICATE中国河北省唐山市乐亭县王滩镇
Wangton, Laoting, Tangshan Hebei
Sales Tel: +86 0315-4958677
Sales Tel: +86 0315-4958137
After-sales Service Tel: +86 0315-4958310
240703H01191

客户名称 CUSTOMER		产品名称 PRODUCT	中低温压力容器碳素钢板 Pressure Vessel Plates for Moderate and Lower Temperature		
收货单位 PURCHASER		客户编号 CUSTOMER NO.	3000160	证书编号 CERTIFICATE NO.	240703H01191
执行标准 SPECIFICATION	ASTM A516/A516M-17; A516 Gr70	出货单号 DELIVERY NO.	124070002	证书日期 T/C ISSUE DATE	20240703
		交货日期 SHIPPING DATE		交货状态 DELIVERY CONDITION	AR-HPR 热轧
		订单编号 ORDER NO.	1000197834	合同号 CONTRACT NO.	24XS-CK-0509(2)
牌号 TRADE NO.	A516 Gr70				

批次号 SAMPLE NO.	炉号 HEAT NO.	尺寸与规格PRODUCT DESCRIPTION			化学成份 (熔炼分析) CHEMICAL ANALYSIS (SMELTING ANALYSIS) %																A1 拉伸试验 G. L. = A200mm		
					C	Mn	S	P	Si	Nb	V	Ti	Cu	Cr	Ni	Mo	B	Als	Ceq	屈服 Y.S.	抗拉 T.S.	伸长 EL	
		尺寸(厚×宽×长) DIMENSION (mm)	数量 PCS	重量 TON	⁻² X10	⁻² X10	⁻³ X10	⁻³ X10	⁻² X10	⁻³ X10	⁻⁴ X10	⁻³ X10	⁻⁴ X10	⁻³ X10	⁻⁴ X10	⁻⁴ X10	⁻³ X10	⁻² X10	N / mm 2	%			
240530X111	4L04870	18 X2500 X12000	2	8.500	16	136	3	16	21	3	45	2	99	28	58	5	6	27	39	385	515	26.0	
240530X113	4L04869	18 X2500 X12000	6	25.657	16	137	3	23	20	3	50	2	97	26	60	1	6	23	40	380	510	26.0	
240530X134	4L04868	16 X2500 X12000	3	11.295	16	139	6	18	18	2	38	2	66	26	51	30	6	22	40	365	510	27.0	
		TOTAL :	11	45.502																			

240530X111 产品号 (PRODUCT NO.): 4530CY011R 4530CY012R

240530X113 产品号 (PRODUCT NO.): 4530CY015R 4530CY016R 4530CY025R 4530CY026R 4530CY065R 4530CY066R

240530X134 产品号 (PRODUCT NO.): 4530CY126R 4530CY127F 4530CY128R

注释
NOTES

$Ceq = C + Mn/6 + (Cr + V + Mo)/5 + (Cu + Ni)/15$
 G. L = Gauge Length A=5.65 √ So
 Y.S = Yield Strength (Rp0.2 or Rt0.5)
 T.S = Tensile Strength
 E. L = Percentage Elongation After Fracture

兹证明本文所列产品, 均依材料标准制造及试验, 并符合标准之要求。
 WE HEREBY CERTIFY THAT MATERIAL DESCRIBED HEREIN HAS BEEN MANUFACTURED AND TESTED WITH SATISFACTORY
 RESULTS IN ACCORDANCE WITH THE REQUIREMENT OF THE ABOVE MATERIAL SPECIFICATION.



质量证明专用章

张锦兴

成品质量负责人
CHIEF OF INSPECTOR

产品质量证明书
MILL TEST CERTIFICATE中国河北省唐山市乐亭县王滩镇
Wangtan, Laoting, Tangshan Hebei
Sales Tel: +86 0315-4958677
Sales Tel: +86 0315-4958137
After-sales Service Tel: +86 0315-4958310
240703H01190

客户名称 CUSTOMER		产品名称 PRODUCT	中低温压力容器碳素钢板 Pressure Vessel Plates for Moderate and Lower Temperature		
收货单位 PURCHASER		客户编号 CUSTOMER NO.	3000160	证书编号 CERTIFICATE NO.	240703H01190
执行标准 SPECIFICATION	ASTM A516/A516M-17; A516 Gr 70	出货单号 DELIVERY NO.	T24070002	证书日期 T/C ISSUE DATE	20240703
		交运日期 SHIPPING DATE		交货状态 DELIVERY CONDITION	AR-HPR-热轧
牌号 TRADE NO.	A516 Gr 70	订单编号 ORDER NO.	1000197834	合同号 CONTRACT NO.	24XS-Ck-0509(2)

TRADE NO.		化学成份 (熔炼分析) CHEMICAL ANALYSIS (SMELTING ANALYSIS) %																		A1 拉伸试验 G. L. =A200mm			
批次号 SAMPLE NO.	炉号 HEAT NO.	尺寸与规格 PRODUCT DESCRIPTION			C	Mn	S	P	Si	Nb	V	Ti	Cu	Cr	Ni	Mo	B	Als	Ceq	屈服 Y.S.	抗拉 T.S.	伸长 EL	
		尺寸(厚×宽×长) DIMENSION (mm)	数量 PCS	重量 TON	⁻³ X10	⁻² X10	⁻³ X10	⁻³ X10	⁻² X10	⁻³ X10	⁻⁴ X10	⁻³ X10	⁻⁴ X10	⁻³ X10	⁻⁴ X10	⁻⁴ X10	⁻⁴ X10	⁻³ X10	⁻² X10	N/mm2	%		
240530X122	4L04871	22 X2500 X12000	7	36.582	16	136	4	20	18	2	37	3	64	22	56	38	6	30	39	415	540	21.0	
240530X123	4L04871	22 X2500 X12000	3	15.651	16	136	4	20	18	2	37	3	64	22	56	38	6	30	39	400	530	20.0	
240530X124	4L04870	22 X2500 X12000	4	20.850	16	136	3	16	21	3	45	2	99	28	58	5	6	27	39	390	520	27.0	
240530X127	4L04869	16 X2500 X12000	9	34.020	16	137	3	23	20	3	50	2	97	26	60	1	6	23	40	380	515	20.0	
240530X130	4L04868	16 X2500 X12000	12	45.210	16	139	6	18	18	2	38	2	66	26	51	30	6	22	40	370	505	24.0	
		TOTAL:	35	152.313																			
240530X122	产品号 (PRODUCT NO.): 4530CY069R 4530CY077R 4530CY078R 4530CY083R 4530CY084R 4530CY087R 4530CY088R																						
240530X123	产品号 (PRODUCT NO.): 4530CY085R 4530CY086R 4530CY142R																						
240530X124	产品号 (PRODUCT NO.): 4530CY091R 4530CY092R 4530CY110R 4530CY111R																						
240530X127	产品号 (PRODUCT NO.): 4530CY099R 4530CY100R 4530CY101R 4530CY102R 4530CY103R 4530CY104R 4530CY108R 4530CY109R 4530CY110R																						
240530X130	产品号 (PRODUCT NO.): 4530CY105R 4530CY106R 4530CY107R 4530CY117R 4530CY118R 4530CY119R 4530CY120R 4530CY121R 4530CY122R 4530CY135R 4530CY136R 4530CY137R																						
注释 NOTES	Ceq=C+Mn/6+(Cr+V+Mo)/5+(Cu+Ni)/15 G. L.= Gauge Length A=5.65√So Y. S.= Yield Strength(Rp0.2 or Rt0.5) T. S.= Tensile Strength E. L.= Percentage Elongation After Fracture																						
	兹证明本文所列产品, 均依材料标准制造及试验, 并符合标准之要求。 WE HEREBY CERTISFY THAT MATERIAL DESCRIBED HEREIN HAS BEEN MANUFACTURED AND TESTED WITH SATISFACTORY RESULTS IN ACCORDANCE WITH THE REQUIREMENT OF THE ABOVE MATERIAL SPECIFICATION.																						
																				质量证明专用章		张锦兴	
																				成品质量负责人 CHIEF OF INSPECTOR			

产品质量证明书
MILL TEST CERTIFICATE中国河北省唐山市乐亭县王滩镇
Wangtan, Laoting, Tangshan Hebei
Sales Tel: +86 0315-4958677
Sales Tel: +86 0315-4958137
After-sales Service Tel: +86 0315-4958310
240703H01189

客户名称 CUSTOMER		产品名称 PRODUCT	中低温压力容器碳素钢板 Pressure Vessel Plates for Moderate and Lower Temperature		
收货单位 PURCHASER		客户编号 CUSTOMER NO.	3000160	证明书编号 CERTIFICATE NO.	240703H01189
执行标准 SPECIFICATION	ASTMA516/A516M-17; A516 Gr70	出货单号 DELIVERY NO.	T24070002	证明书日期 T/C ISSUE DATE	20240703
		交运日期 SHIPPING DATE		交货状态 DELIVERY CONDITION	AR-HPR-热轧
牌号 TRADE NO.	A516 Gr70	订单编号 ORDER NO.	1000197834	合同号 CONTRACT NO.	24XS-CK-0509(2)

批次号 SAMPLE NO.		炉号 HEAT NO.		尺寸与规格 PRODUCT DESCRIPTION			化学成份 (熔炼分析) CHEMICAL ANALYSIS (SMELTING ANALYSIS) %															A1 拉伸试验 G. L. = A200mm			
				尺寸(厚×宽×长) DIMENSION (mm)	数量 PCS	重量 TON	C	Mn	S	P	Si	Nb	V	Ti	Cu	Cr	Ni	Mo	B	Ceq	Als	屈服 Y.S.	抗拉 T.S.	伸长 EL	
							⁻² X10	⁻² X10	⁻³ X10	⁻³ X10	⁻² X10	⁻³ X10	⁻⁴ X10	⁻³ X10	⁻⁴ X10	⁻³ X10	⁻⁴ X10	⁻⁴ X10	⁻⁴ X10	⁻² X10	⁻³ X10	N/mm ²	%		
240531X352		4L04909		10 X 2500 X 12000	9	21.525	17	139	7	15	18	1	37	1	75	25	59	0	5	41	25	405	530	22.0	
240531X362		4L04867		12 X 2500 X 12000	8	22.800	17	137	5	19	20	2	41	3	64	25	52	32	6	41	31	370	520	24.0	
				TOTAL:	17	44.325																			
240531X352		产品号 (PRODUCT NO.): 4531DY475R 4531DY476R 4531DY479R 4531DY480R 4531DY481R 4531DY482R 4531DY483R 4531DY485R 4531DY486R																							
240531X362		产品号 (PRODUCT NO.): 4531DY520R 4531DY521R 4531DY522R 4531DY529R 4531DY530R 4531DY531R 4531DY532R 4531DY533R																							
注释 NOTES		Ceq=C+Mn/6+(Cr+V+Mo)/5+(Cu+Ni)/15 G. L= Gauge Length A=5.65√So Y.S= Yield Strength(Rp0.2 or Rt0.5) T.S= Tensile Strength E. L= Percentage Elongation After Fracture																							
兹证明本文所列产品, 均依材料标准制造及试验, 并符合标准之要求。 WE HEREBY CERTISFY THAT MATERIAL DESCRIBED HEREIN HAS BEEN MANUFACTURED AND TESTED WITH SATISFACTORY RESULTS IN ACCORDANCE WITH THE REQUIREMENT OF THE ABOVE MATERIAL SPECIFICATION.																									
																							 质量证明专用章 张锦兴 成品质量负责人 CHIEF OF INSPECTOR		